



Material NO. 4611110032419

Unit: mm



接线图
Wiring Diagram



励磁顺序 vs. 旋转方向
Exciting Sequence vs.
Direction of Rotation

STEP	A	B	C	D	Backward
1	+	+	-	-	↑
2	-	+	+	-	
3	-	-	+	+	
4	+	-	-	+	


从安装面看为顺时针方向
Clockwise view from
mounting side

规格
Specifications

1	相数 Number Of Phase	2
2	步长 Linear Travel/Step	0.0127 mm (1.8°)
3	额定电压 Rated Voltage	4.1 V DC
4	额定电流 Rated Current	0.67 Amp
5	额定推力 Rated Thrust	28 N(@300rpm, rated current)
6	相电阻 Phase Resistance	6.1 ohm ±10% (20°C)
7	相电感 Phase Inductance	5.5 mH ±20% (1kHz 1V rms)
8	转子惯量 Rotor Inertia	9 gcm ²
9	重量 Weight	0.1 Kg
10	绝缘等级 Insulation Class	B(130°C)
11	丝杠直径 Screw Diameter	4.76 mm
12	丝杠导程 Lead	2.54 mm

版本变更

版本	变更说明	签名	日期
----	------	----	----



连接器针位 vs. 引线颜色
Pin No. vs. Lead Wire Colour

Pin No.	颜色 Colour
1	黑 BLA
3	绿 GRN
4	红 RED
6	蓝 BLU

电机标签
Motor label

LEAD SCREW MOTOR
LC111S-E04025-38-S-067
XXXXXXX

批次号

备注Note:
螺纹丝杆在正常使用过程中,
若有少许粉尘掉落为正常现象。
It's normal phenomenon if there is a little dust
fall off when using the lead screw and nut.

未标注线性尺寸和公差 Tolerance for linear and dimensions without individual tolerance indications GB/T 1804-M eqv ISO 2768-1:M	设计 Design	杨淑娟	2019/2/27	First Angle Method	PBC+MOONS' 上海市闵行区 鸣嘉路168号 上海鸣志派博思自动化技术有限公司 (021)52634688
	校核 Check				
	工艺 Process			材料 Material	总图
	标准化 Standard				
I. 请避免螺母脱离丝杠 Keep nut on screw. II. 非专业人士请勿拆解电机 Avoid disassembly without qualification.	批准 Approve			Page 1 of 1	版本 Version A0
					比例 Scale 1:1
					零件名 Part Name 直线步进电机
					型号 Model NO. LC111S-E04025-38-S-067
					物料号 Material NO. 4611110032419